

LED CoolerTube External Driver — 4/5/6-ft



Key Features

- Efficacy > 95 LPW (clear lens)
- CCT: 3000K, 3500K, 4000K, 4500K, 5000K
- CRI > 80
- **IP65 rating** for moisture proof
- Beam angle: **170°**
- Power factor > .90
- Lens type: clear
- Driver type: external driver
- Driver input voltage: 100V-277VAC (50-60Hz)
- Drive output voltage: 36V DC
- Operating temperature: -20°F to 122°F
- Rated life: up to 50,000 hours
- Warranty: 5 years
- Length: 4-ft, 5-ft, 6-ft
- Certification: **cULus, DLC**

Description

Aleddra, with its strong industry reputation with the EasiRetrofit® LED tube for T12/T8 replacement, is now offering an LED alternative for refrigerator lighting. The new CoolerTube is designed with 170 degree beam angle, meeting perfectly the needs of merchandise lighting on both side of the LED light, while maintaining a high efficacy at 95 lm/w and a power factor 0.90. These features far exceed any competitive products on the market.

The CoolerTube is both cULus and DLC certified, and is qualifies for utility rebates. It comes in five different colors, clear lens, and three sizes: 4-ft, 5-ft and 6-ft. It is rated for 50,000 hours and has a 5-year warranty. Its low DC voltage external driver removes any electric shock hazard during installation and maintenance.

National grocers, supermarkets, and convenience stores are the perfect target customer for the CoolerTube for use in coolers and refrigerators. In addition, they benefit from Aleddra's EasiRetrofit T8 LED tube for their ceiling lighting.

Ordering Information

Product Label*	Length	Lens	Color Temperature
LLT-4-FR-C-22W-35K	4-ft	C	3500K
LLT-4-FR-C-22W-40K	4-ft	C	4000K
LLT-4-FR-C-22W-45K	4-ft	C	4500K
LLT-4-FR-C-22W-50K	4-ft	C	5000K
LLT-5-FR-C-22W-35K	5-ft	C	3500K
LLT-5-FR-C-22W-40K	5-ft	C	4000K
LLT-5-FR-C-22W-45K	5-ft	C	4500K
LLT-5-FR-C-22W-50K	5-ft	C	5000K
LLT-6-FR-C-30W-35K	6-ft	C	3500K
LLT-6-FR-C-30W-40K	6-ft	C	4000K
LLT-6-FR-C-30W-45K	6-ft	C	4500K
LLT-6-FR-C-30W-50K	6-ft	C	5000K