

CF-LED® Lamp

E26, GX23-2, G24Q, GU24 bases



Specifications

Efficacy	120 LPW
Socket Type	E26, GU24 GX23-2 (2-pin), G24Q, (4-pin)
Color	3000K, 4000K, 5000K
CRI	> 80
Input Voltage	110V-277V
Operating Temp.	-20°F to 122°F
Wattage	6W, 11W
Beam Angle	360°
Warranty	5-year warranty

aleddra

425.430.4555 | info@aleddra.com | sales@aleddra.com | www.aleddra.com

Features

- 50% energy saving and 75% maintenance reduction
- Cost-effective
- Rated for enclosed fixture
- GX23-2 & G24Q bases are dual-mode: ballast-compatible and line voltage friendly
- E26 & GU24 bases are line voltage friendly
- Can be installed horizontally or vertically with the same beam spread as traditional lamps
- 5-year warranty

Product Compliance & Certifications:

- UL and cUL Type A/Type B listed (OOLV/OOLV7.E479597)
- UL and cUL classified (IFAR/IFAR7.E325073)
- LDL Pending

Description

Aleddra's CF-LED® lamp offers the first 360-degree LED PL lamp with 100 lm/w efficacy. Unlike other LED PL lampson the market today, this revolutionary lamp can be installed either vertically or horizontally with the same beam spread as traditional lamps.

Size

6W: 1 3/8"W x 1 3/8"L x 4.5"H
(top to socket edge, not including the in-socket length)

11W: 1 3/8"W x 1 3/8"L x 6.1"H
(top to socket edge, not including the in-socket length)

Ordering Information (GX23-2/G24Q)

Model #	Socket	Lumen	Wattage	Replace HID Wattage	Color
APL-6-D-GX23-2-30K	GX23-2	790lm	6W	13W	3000K
APL-6-D-GX23-2-40K	GX23-2	790lm	6W	13W	4000K
APL-6-D-GX23-2-50K	GX23-2	790lm	6W	13W	5000K
APL-11-D-GX23-2-30K	GX23-2	1240lm	11W	26W	3000K
APL-11-D-GX23-2-40K	GX23-2	1240lm	11W	26W	4000K
APL-11-D-GX23-2-50K	GX23-2	1240lm	11W	26W	5000K
APL-6-D-G24Q-30K	G24Q	790lm	6W	13W	3000K
APL-6-D-G24Q-40K	G24Q	790lm	6W	13W	4000K
APL-6-D-G24Q-50K	G24Q	790lm	6W	13W	5000K
APL-11-D-G24Q-30K	G24Q	1240lm	11W	26W	3000K
APL-11-D-G24Q-40K	G24Q	1240lm	11W	26W	4000K
APL-11-D-G24Q-50K	G24Q	1240lm	11W	26W	5000K

Ordering Information (E26/GU24)

Model #	Socket	Lumen	Wattage	Replace HID Wattage	Color
APL-6-A-E26-30K	E26	790lm	6W	13W	3000K
APL-6-A-E26-40K	E26	790lm	6W	13W	4000K
APL-6-A-E26-50K	E26	790lm	6W	13W	5000K
APL-11-A-E26-30K	E26	1240lm	11W	26W	3000K
APL-11-A-E26-40K	E26	1240lm	11W	26W	4000K
APL-11-A-E26-50K	E26	1240lm	11W	26W	5000K
APL-6-A-GU24-30K	GU24	790lm	6W	13W	3000K
APL-6-A-GU24-40K	GU24	790lm	6W	13W	4000K
APL-6-A-GU24-50K	GU24	790lm	6W	13W	5000K
APL-11-A-GU24-30K	GU24	1240lm	11W	26W	3000K
APL-11-A-GU24-40K	GU24	1240lm	11W	26W	4000K
APL-11-A-GU24-50K	GU24	1240lm	11W	26W	5000K