

## CF-LED™ Lamp

— E26, GX23-2, G24Q, GU24 bases



## Key Features

- Efficacy: 100 LPW
- Dual-mode: ballast-compatible and line voltage friendly
- Socket type: E26, GX23-2 (2-pin), G24Q (4-pin), GU24
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- CRI > 80
- Beam angle: 360°
- Input voltage: 110V-277V
- Wattage: 6W, 11W
- Operating temperature: -20°F to 122°F
- Warranty: 5 years
- UL/LDL pending
- Patent Pending

## Description

**Aleddra's** CF-LED™ lamp offers the first 360-degree LED PL lamp with 100 lm/w efficacy. Unlike other LED PL lamps on the market today, this revolutionary lamp can be installed either vertically or horizontally with the same beam spread as traditional lamps. Its frosted glass filters most of the blue color light that's harmful to human eyes.

This CF-LED lamp operates with 110 to 277V AC line voltage with or without a ballast. It is immediately available in E26 medium base, 2-pin GX23-2 base, 4-pin G24Q base, and GU24 base, and at 6W (for 13W CFL replacement) and 11 wattage (for 26W CFL replacement).

The default color options are 2700K, 3000K, 3500K, 4000K, and 5000K. It comes with 5-year warranty.

### Size:

- 6W: 1 3/8"W x 1 3/8"L x 4.5"H (top to socket edge, not including the in-socket length)
- 11W: 1 3/8"W x 1 3/8"L x 6.1"H (top to socket edge, not including the in-socket length)

## Ordering Information

Product Label	Socket	Lumen	Wattage	Replace CFL Watt.
APL-6-A-E26-XXK*	E26	600 lm	6W	13W
APL-11-A-E26-XXK*	E26	1100 lm	11W	26W
APL-6-D-GX23-2-XXK*	GX23-2	600 lm	6W	13W
APL-11-D-GX23-2-XXK*	GX23-2	1100 lm	11W	26W
APL-6-D-G24Q-XXK*	G24Q	600 lm	6W	13W
APL-11-D-G24Q-XXK*	G24Q	1100 lm	11W	26W
APL-6-A-GU24-XXK*	GU24	600 lm	6W	13W
APL-11-A-GU24-XXK*	GU24	1100 lm	11W	26W

- XXK: 27K, 30K, 35K, 40K, and 50K color

