



Specifications

Efficacy	≥ 126 LM/W
Color	30K (50W), 35K, 40K, 50K
CRI	> 80
Input Voltage	110V-277V
Operating Temp.	-20°F-122°F
Power Factor	>0.90
Size	2x2: 22.52"L x 20.67"W x 2.6"H 2x4: 46.61"L x 20.67"W x 2.6"H
Weight	2x2 at 5.3lbs 2x4 at 10.8lbs
Dimming	0-10V dimmable
Warranty	7-year (10-year optional)

Ordering Information

Product #	Size	Wattage	Lumen	Color
AT-R4-15W-XDZ-35K	2x2	15W	2025	3500K
AT-R4-15W-XDZ-40K	2x2	15W	2025	4000K
AT-R4-15W-XDZ-50K	2x2	15W	2025	5000K
AT-R4-25W-XDZ-35K	2x2	25W	3300	3500K
AT-R4-25W-XDZ-40K	2x2	25W	3300	4000K
AT-R4-25W-XDZ-50K	2x2	25W	3300	5000K
AT-R4-36W-XDZ-35K	2x2	36W	5000	3500K
AT-R4-36W-XDZ-40K	2x2	36W	5000	4000K
AT-R4-36W-XDZ-50K	2x2	36W	5000	5000K
AT-R7-25W-XDZ-35K	2x4	25W	3375	3500K
AT-R7-25W-XDZ-40K	2x4	25W	3375	4000K
AT-R7-25W-XDZ-50K	2x4	25W	3375	5000K
AT-R7-36W-XDZ-35K	2x4	36W	5000	3500K
AT-R7-36W-XDZ-40K	2x4	36W	5000	4000K
AT-R7-36W-XDZ-50K	2x4	36W	5000	5000K

Features

- Easy installation, no screw needed
- 0-10V Dimmable
- Certified for utility rebate

Product Compliance & Certifications:

- UL
- DLC 4.2 Premium

Description

Aleddra's EasiFit® Troffer Retrofit Kit is an energy-efficient and cost-effective replacement for an existing linear troffer luminaire. It fits into the existing troffer housing, saving the labor of removing it and the trouble of disposing it. At the same time, it provides a more aesthetic appearance than the old fixture. The 0-10V dimming makes it controllable by the daylighting harvest system for further energy savings.

The EasiFit® Troffer Kit is UL/DLC certified for utility rebate.

Photos

