

# LED Flood Light

40W, 70W



## Specifications

<b>Driver</b>	Meanwell driver
<b>Efficacy</b>	85-95 LM/W
<b>Color</b>	30K, 40K, 50K
<b>Wattage</b>	30W to 600W
<b>CRI</b>	> 70
<b>Input Voltage</b>	110V-277V (50-60Hz)
<b>Operating Temp.</b>	-40°F-122°F
<b>Power Factor</b>	>0.90
<b>Warranty</b>	5-year warranty

## Ordering Information

Product #	Wattage	Lumen	Weight
AL-FL220-W030-60-30K	30W	2650	3.4
AL-FL220-W030-60-40K	30W	2900	3.4
AL-FL220-W030-60-50K	30W	3000	3.4
AL-FL280-W050-60-30K	50W	4300	7.0
AL-FL280-W050-60-40K	50W	4550	7.0
AL-FL280-W050-60-50K	50W	4700	7.0
AL-FL330-W100-60-30K	100W	8700	10.1
AL-FL330-W100-60-40K	100W	9500	10.1
AL-FL330-W100-60-50K	100W	10000	10.1
AL-FL390-W140-60-30K	140W	12800	18.0
AL-FL390-W140-60-40K	140W	13700	18.0
AL-FL390-W140-60-50K	140W	14000	18.0
AL-FL390-W210-60-30K	210W	18000	24.9
AL-FL390-W210-60-40K	210W	19400	24.9
AL-FL390-W210-60-50K	210W	20000	24.9
AL-FL675-W400-60-30K	400W	43200	48.0
AL-FL675-W400-60-40K	400W	45000	48.0
AL-FL675-W400-60-50K	400W	46000	48.0
AL-FL675-W600-60-30K	600W	57000	62.8
AL-FL675-W600-60-40K	600W	59600	62.8
AL-FL675-W600-60-50K	600W	61000	62.8

## Features

- Compact and light weight, wide range of wattage
- Higher wattage models can be used for sports field lighting
- Samsung LED doides
- Yoke mount bracket with easy lighting direction adjustment
- IP65 for wet location

## Product Compliance & Certifications:



- ETL
- DLC

## Description

Aleddra's LED Flood Light is designed with versatility in mind. It's compact and light weight. It comes in a wide range of wattage, from 30W to 600W, for all types of outdoor lighting applications. The higher wattage models can be used for sports field lighting. Its yoke mount bracket provides easy adjustment for different lighting direction. When mounting on the building, it can be used as a good wallpack fixture. It can also be used on the ground or as a wall wash light. The default beam angle is 60 degrees. We also offer many other beam angles on a made-to-order basis.






YR-FL675-W400



400W: 28"H x 21"W



YR-FL675-W600



600W: 28"H x 27"W

aleddra

425.430.4555 | info@aleddra.com | sales@aleddra.com | www.aleddra.com