

LED Panel Lights

2x2, 2x4



Specifications

Input Wattage	30W, 48W
Efficacy	125 LM/W
CRI	>80
Color	3500K, 4000K, 5000K
Power Factor	>0.9
Input Voltage	100V-277V
Operating Temp.	-4°F-104°F
Size	2'x2', 2'x4'
Warranty	5-year/50,000 hours

Ordering Information

Product #	Wattage	Lumen	Size	Color
AL-PL40D2235H	30W	3750lm	2'x2'	3500K
AL-PL40D2240H	30W	3750lm	2'x2'	4000K
AL-PL40D2250H	30W	3750lm	2'x2'	5000K
AL-PL54D2435H	48W	6000lm	2'x4'	3500K
AL-PL54D2440H	48W	6000lm	2'x4'	4000K
AL-PL54D2450H	48W	6000lm	2'x4'	5000K

Features

- Easy and quick to install
- Suitable for retrofit and new construction
- Suitable for use in damp locations
- Suitable for standard T-Bar lay-in or suspended mount applications
- 0-10V Dimmable
- Rated lifetime of 50,000 hours

Product Compliance & Certifications:

- UL

Description

Aleddra's LED Panel Light is an energy-efficient and cost-effective replacement for traditional linear fluorescents. It utilizes edge lighting technology to enable ultra-thin and ultra-light fixtures with uniform lighting effect. It is designed for visual comfort and provides a pleasing environment while qualifying for the highest classification of utility rebates. Clean and elegant designs make them ideally suited for all types of interior space including offices, schools, hospitals, elder care facilities and retail locations.