



Specifications

Lens Type	clear
Driver Type	external driver
Input Voltage	100V-277VAC (50-60Hz)
Output Voltage	36V DC
Efficacy	> 95 LPW (clear lens)
Color	30K, 35K, 40K, 45K, 50K
CRI	> 80
Operating Temp.	-20°F-122°F
Power Factor	> .90
Beam Angle	170°
Warranty	5-year

Ordering Information

Product #	Length	Lens	Color
LLT-4-FR-C-22W-35K	4-ft	Clear	3500K
LLT-4-FR-C-22W-40K	4-ft	Clear	4000K
LLT-4-FR-C-22W-50K	4-ft	Clear	5000K
LLT-5-FR-C-22W-35K	4-ft	Clear	3500K
LLT-5-FR-C-22W-40K	5-ft	Clear	4000K
LLT-5-FR-C-22W-50K	5-ft	Clear	5000K
LLT-6-FR-C-30W-35K	6-ft	Clear	3500K
LLT-6-FR-C-30W-40K	6-ft	Clear	4000K
LLT-6-FR-C-30W-50K	6-ft	Clear	5000K

Features

- Qualifies for Utility Rebates
- IP65 rating for moisture proof
- LED alternative for refrigerator lighting
- National grocers, supermarkets, and convenience stores are the perfect target audience for the CoolerTube

Product Compliance & Certifications:

- cULus
- DLC

Description

Aleddra, with its strong industry reputation with the EasiRetrofit® LED tube for T12/T8 replacements, is now offering an LED alternative for refrigerator lighting.

The CoolerTube is designed with a 170 degree beam angle, meeting the needs of merchandise lighting on both sides of the LED light, while maintaining a high efficacy at 95 lm/w and a power factor 0.90.

National grocers, supermarkets, and convenience stores are the perfect target customer for the CoolerTube. It is used in coolers and refrigerators. In addition they benefit from Aleddra's EasiRetrofit T8 LED tube for their ceiling lighting.

The features of the CoolerTube exceed any competitive products on the market.