

Slim Lowbay Canopy

40W, 70W



Specifications

| | |
|------------------------|--------------------|
| Driver | Meanwell driver |
| Efficacy | ≥ 105 LM/W |
| Color | 5000K |
| CRI | > 80 |
| Input Voltage | 110V-277V |
| Power Factor | >0.95 |
| Operating Temp. | -40°F-122°F |
| Rated Life | up to 50,000 hours |
| Warranty | 5-year warranty |

Ordering Information

| Product # | Wattage | Lumen | Replacing | Weight |
|----------------|---------|-------|-----------|--------|
| ACP-24-40W-50K | 40W | 4300 | 150W | 5.5lbs |
| ACP-24-70W-50K | 70W | 7750 | 250W | 6.4lbs |

* 5000K in stock, other colors made to order

Dimension: 10.5" x 10.5" x 4"

Features

- Energy-efficient & cost-effective replacement for existing traditional lowbay canopy luminaire
- Built with top of the line LEDs and the reputable Meanwell driver
- IP65 wet location
- Die-cast aluminum housing
- Ideal for parking garage or low-ceiling canopy lighting applications
- Mounting Options: Surface mount, Pole mount, Base-plate mount

Product Compliance & Certifications:

- UL
- DLC 4.0

Description

Aleddra's Slim Lowbay Canopy Luminaire is an energy efficient and cost-effective replacement for an existing traditional lowbay canopy luminaire. It's built with top of the line LEDs and the reputable Meanwell driver, which means, fewer maintenance costs.

Its IP65 rating makes it ideal for wet locations. The Slim Lowbay Canopy Luminaire is UL certified and DLC qualified for utility rebate. It comes with a 5-year, 50,000 hours warranty.

The application is ideal for parking garage or low-ceiling canopy lighting applications.



Option A: Surface Mount



Option B: Pole Mount



Option C: Base-plate mount