



Vandal Guard



Light Guard



## Features

- More than 85% light transmission glass lens
- Application: outdoor walkways, security lighting, building entrances, schools, museum and commercial building
- Back fins on base cover, providing efficient heat dissipation
- Photocell installed by default
- 0-10V dimmable for great energy savings
- Light guard for dark-sky compliance (optional)
- Vandal protection guard (optional)
- Photo control and motion sensor (optional)
- 5-year warranty

### Product Compliance & Certifications:

- UL, DLC 4.2
- IP65 rated

## Description

The Quick Mounting Wall Pack is an energy-efficient and cost-effective replacement for the existing wallpack luminaire. Ideal for wet location with its IP65 rating. Superior die-cast aluminum housing with high-durability and long lasting color. A light guard can be attached to the fixture for dark-sky compliant application. Vandal protection guard is also available.

## Specifications

<b>Efficacy</b>	100-115 lm/w
<b>Color</b>	5000K
<b>CRI</b>	>80
<b>Input Voltage</b>	110V-277V
<b>Operating Temp.</b>	-40°F-140°F
<b>Wattage</b>	40W, 60W, 80W, 120W
<b>Power Factor</b>	>0.94
<b>Photocell</b>	Built-in
<b>Dimmable</b>	0-10V
<b>Rated Life</b>	up to 76,000 hours
<b>Warranty</b>	5-year warranty

### Size

40/60W: 9.25" x 14.3"  
90/120W: 8.9" x 18.3"

## Ordering Information

Product #	Wattage	Lumen	Color
AWP-WPL-4-40W-50K	40W	4320lm	5000K
AWP-WPL-4-60W-50K	60W	6545lm	5000K
AWP-WPL-4-90W-50K	90W	9800lm	5000K
AWP-WPL-4-120W-50K	120W	12720lm	5000K

## Dimensions

