



## Features

- Stylish lens-less design
- Patent-pending nano-reflector for indirect lighting
- Uniform light distribution
- Free of hot-spot
- Rated for commercial installation
- Installation with or without a recess can
- 3-year warranty / 30,000 hours

## Specifications

<b>Size</b>	5" / 7.5"
<b>Input Voltage</b>	110-277V
<b>Wattage</b>	9W, 12W
<b>Color</b>	30K and 40K (other color made to order)
<b>Light Output</b>	700 - 950 lm
<b>CRI</b>	> 80
<b>Beam Angle</b>	120°
<b>Operating Temp.</b>	-4 °F to 122 °F
<b>Rated Life</b>	30,000 hours
<b>Warranty</b>	3-year


## Product Compliance & Certifications:

- UL


## Description

Aleddra's SureFit® LED Downlight is a high performance and cost-effective option for commercial and residential ceiling lighting applications. This downlight comes with an E26 straight wire connection and mounting hardware, installation is quick and easy and does not require the help of a professional. With its superior efficacy and a longer life than compact fluorescents, it provides soft white light to create a comfortable and relaxing environment.

The downlight comes with two sets of springs. Spring A set is for installation with existing recess can, whereas Spring B set is for installation without recess can, i.e., directly to the ceiling.



Spring A



Spring B

## Ordering Information

Product Model #	Color	Wattage	Light Output	Dimensions	Dimmable*
AL-SELD31US2-830-9-E26-D	30K	9W	700 lm	5" x 2.5"	Yes
AL-SELD31US2-840-9-E26-D	40K	9W	730 lm	5" x 2.5"	Yes
AL-SELD31US2-830-12-E26-D	30K	12W	910 lm	7.5" x 2.9"	Yes
AL-SELD31US2-840-12-E26-D	40K	12W	950 lm	7.5" x 2.9"	Yes
AL-SELD31US2-830-12-E26	30K	12W	910 lm	7.5" x 2.9"	No
AL-SELD31US2-840-12-E26	40K	12W	950 lm	7.5" x 2.9"	No

\* Supporting 120V TRIAC dimmer only.