



1000W

1250W

250W

500W

750W

## Specifications

<b>Wattage</b>	250W, 500W, 750W, 1000W, 1250W
<b>Color Temp.</b>	5000K
<b>CRI</b>	> 70
<b>Input Voltage</b>	AC100-277V/240-480V
<b>Operating Temp.</b>	-22°F to 122°F
<b>IP Rating</b>	IP66
<b>Efficacy</b>	130~150LM/W
<b>Power Factor</b>	> 0.95
<b>Beam Angle</b>	10°/ 30°/ 60°/ 120°/ 150°*60°/ T3-VS
<b>Rated Life</b>	50,000 hours
<b>Warranty</b>	5-year warranty

## Features

- Compact and light weight
- Wide range of wattage from 250W to 1500W
- High power & wide beam angle
- 120 and 150 degree lens
- Cost-effective
- 5-year warranty

## Product Compliance & Certifications:

- UL Listed
- DLC Listed
- IP65 Rated

## Description

Aleddra's Gen2 High Power Flood Light is designed with versatility in mind. It is a good option when you need a high-power & wide-beam-angle fixture. This Flood Light can go up to 120 and 150 degree lens. It's compact and light-weight, and with a wide range for wattage, from 250W to 1250W, for all types of outdoor lighting applications.

## Ordering Information

Model #	Wattage	Lumen	Dimensions
HD-FL02-250WD-D5000K (277V)	250W	32,500~37,500LM	45.1"x20"x5.36"
HD-FL02-500WD-D5000K (277V)	500W	65,000~75,000LM	45.1"x20"x5.36"
HD-FL02-750WD-D5000K (277V)	750W	97,500~112,500LM	19"x11.65"x5.3"
HD-FL02-1000WD-D5000K (277V)	1000W	130,000~150,000LM	19"x11.65"x5.3"
HD-FL02-1250WD-D5000K (277V)	1250W	162,500~187,500LM	22.2"x20"x5.36"
HD-FL02-250WD-S-D5000K (480V)	250W	32,500~37,500LM	22.2"x20"x5.36"
HD-FL02-500WD-S-D5000K (480V)	500W	65,000~75,000LM	30.1"x20"x5.36"
HD-FL02-750WD-S-D5000K (480V)	750W	97,500~112,500LM	30.1"x20"x5.36"
HD-FL02-1000WD-S-D5000K (480V)	1000W	130,000~150,000LM	38"x20"x5.36"
HD-FL02-1250WD-S-D5000K (480V)	1250W	162,500~187,500LM	38"x20"x5.36"