



Specifications

Emergency Power	25W, 40W
Emergency Time	90 minutes
Battery Type	Lithium or Ni-MH
Input Voltage	AC100-347V
Output Voltage	170Vdc
Operating Temp.	32°F to 122°F
Surge Protection	Line-Neutral 3KV

Description

Aleddra's UFO Emergency Battery Pack provides 25W/40W lumen output during emergency illumination for a minimum of 90 minutes. It is a cost-effective and energy-efficient option for various emergency lighting applications such as warehouses, manufacturing facilities, school gymnasiums, community centers, recreation centers, and department stores.

Ordering Information

Model #	Emergency Power	Recommended for
EMUFO-25170-TT	25W	100W and 150W UFO
EMUFO-40170-TT	40W	200W, 240W, 300W UFO

Features

- Automatic Battery Testing: 30 seconds test monthly and 90 minutes test annually
- Emergency Operation: 90 minutes
- Low energy consumption CEC Title20 compliance
- Constant power output on emergency mode
- One Piece Design with Metal Housing
- Battery
 - Over Temperature Protection
 - Over Charge Protection
 - Over Discharge Protection
- Battery testing with remote control for up to 98ft distance (optional)

Product Compliance & Certifications:

- UL Listed
- UL924 Listed and tested to CSA C22.2 NO.141 Field or factory installation
- NFPA 101 (Life Safety Code)

Installation Kit: (included)



(1) Hanging Hook Bolt
(1) Hanging Ring Bolt



(1) Safe Wire with chain link connector



(11) pcs Wire Endcap



(2) pcs Connector Suitable for wire diameter 0.118-0.248" (3-6.3mm) (Optional)
(2) pcs Connector Suitable for wire diameter 0.196-0.393" (5-10mm) (Optional)



(1) Remote Control (Optional)